

Qty	Part Number	Size I.D. (in)	A±1/8 (in)	Pressure* (PSI)	Weight (Lbs)	Project Info
	MMCC0200	2	9	455	9	
	MMCC0250	2-1/2	9	345	13	
	MMCC0300	3	9	289	14	
	MMCC0400	4	9	300	18	
	MMCC0500	5	11	220	25	
	MMCC0600	6	11	200	28	
	MMCC0800	8	12	190	52	
	MMCC1000	10	13	150	75	
	MMCC1200	12	14	125	105	
	MMCC1400	14	14	105	115	

*For safe working pressure above 70°F, multiply the pressure shown at 70°F times the correction factor of the required temperature.

Temperature (°F)	Factor
70	1.0
200	.92
300	.86
400	.82
500	.77
600	.73

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

LEAD FREE
The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

DATE

	Metra le	2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM
CUSTOMER:	METRA	- MINI
DDO IFOT.	STAINLESS STEEL PU	MP CONNECTOR
PROJECT:	DRAWN BY: DKISH	DATE: 1/10/2014
	APPROVED: JC	DATE: 1/10/2014
ENGINEER:	SCALE: DRAWING NUMBE	R:
	NONE	MMCC

REV.