



Qty	Part Number	Size (in)	A (in)	B (in)	PSI @ 70°F	Project Info
	SDFS900200	2	10-1/2	2-1/4	455	
	SDFS900250	2-1/2	11	2-3/4	345	
	SDFS900300	3	11-1/2	3-1/4	289	
	SDFS900400	4	12-1/2	4-1/4	300	
	SDFS900500	5	15-1/2	5-1/4	220	
	SDFS900600	6	16-1/2	6-1/4	200	
	SDFS900800	8	19-1/4	8-1/4	190	
	SDFS901000	10	22-1/4	10-1/4	150	
	SDFS901200	12	25-1/4	12-1/4	125	
	SDFS901400	14	27-1/4	14-1/4	105	

MAX PERMANENT OFFSET FROM CENTERLINE - 3/8"  
MAX INTERMITTENT OFFSET FROM CENTERLINE - 1/8"

\*For safe working pressure above 70°F,  
multiply pressure shown at 70°F by  
correction factor of required temp.

Temperature (°F)	Factor
70	1.00
200	0.92
300	0.86
400	0.82
500	0.77
600	0.73

### LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV. 1	VANE STAINLESS	DATE 12/3/2013
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM
Suction Diffuser Flex with 150# Plate Flange and a S.R. Elbow		
DRAWN BY: <b>DKISH</b>		DATE: <b>11/22/2013</b>
APPROVED: <b>JC</b>		DATE: <b>11/22/2013</b>
SCALE: <b>NONE</b>	DRAWING NUMBER: <b>SDFS90</b>	