





STANDARD SCREENS

Service	Sizes (in)	Perf. (in)
Steam	2 - 10	.045
	12	.062
Liquid	2 - 4	.062
	5 - 12	.125

Qty	Part Number	Size I.D. (in)	A (in)	B (in)	Blowoff Size (in)	Weight (Lbs)	Project Info
	M2K0200	2	9-5/16	6	1/2	26	
	M2K0250	2-1/2	11-1/16	7-1/8	1	40	
	M2K0300	3	12-5/8	9-1/8	1-1/4	59	
	M2K0400	4	15-5/8	10-7/8	1-1/2	93	
	M2K0500	5	18-1/4	12-15/16	2	146	
	M2K0600	6	20-3/16	14-1/2	2	194	
	M2K0800	8	25-1/8	16-7/16	2	316	
	M2K1000	10	29-1/8	19-1/4	2	475	
	M2K1200	12	33-3/4	22-7/8	2	750	

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

OPERATING TEMPERATURE AND PRESSURE:

Steam..... 250 psi at 450 °F
Water, Oil, Gas..... 500 psi at 100 °F

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL M2K Y-TYPE 250# FLANGED STRAINER	
DRAWN BY: DKISH	DATE: 12/27/2013
APPROVED: JC	DATE: 12/27/2013
SCALE: NONE	DRAWING NUMBER: M2K