



FOR TEMPERATURES ABOVE 70° F	
TEMP. °F.	FACTOR
70	1.00
200	.92
300	.86
400	.82
500	.77
600	.72

* FOR SAFE WORKING PRESSURE ABOVE 70° F. MULTIPLY PRESSURE SHOWN AT 70° F. TIMES CORRECTION FACTOR OF REQUIRED TEMP.

QTY.	A PIPE SIZE	B PIPE SIZE	C FACE to FACE	PRESS. @ 70° F.*	NOTES
	2.5"	3"	9"	345	
	2.5"	4"	9"	345	
	3"	4"	9"	289	
	3"	5"	9"	289	
	4"	5"	9"	300	
	4"	6"	9"	300	
	5"	6"	11"	220	
	5"	8"	11"	220	
	6"	8"	11"	200	
	6"	10"	11"	200	
	8"	10"	12"	190	
	8"	12"	12"	190	
	10"	12"	13"	150	

MAXIMUM PERMANENT OFFSET FROM $\text{C} \pm 3/8"$
 MAXIMUM INTERMITTENT OFFSET FROM $\text{C} \pm 1/8"$

CUSTOMER _____
 PROJECT _____
 ENGINEER _____
 ARCHITECT _____
 PRO. OR P.O. NO _____



DESCRIPTION:
MODEL RSS
REDUCING STAINLESS STEEL PUMP CONNECTOR

DRAWN BY: JRR	DATE: 12/1/95	DRAWING NO: 150 RSS
-------------------------	-------------------------	-------------------------------